

● PRINTER RUSH ●

(PTO ASSISTANCE)

Application : <u>09750304</u>	Examiner : <u>Be/10</u>	GAU : <u>2633</u>
From: <u>MPB</u>	Location: <u>IDC</u> FMF FDC	Date: <u>11/15/05</u>

Tracking #: epm 09750304 Week Date: 08/08/05

DOC CODE	DOC DATE	MISCELLANEOUS
<input type="checkbox"/> 1449	_____	<input type="checkbox"/> Continuing Data
<input type="checkbox"/> IDS	_____	<input type="checkbox"/> Foreign Priority
<input type="checkbox"/> CLM	_____	<input type="checkbox"/> Document Legibility
<input type="checkbox"/> IIFW	_____	<input type="checkbox"/> Fees
<input type="checkbox"/> SRFW	_____	<input type="checkbox"/> Other
<input type="checkbox"/> DRW	_____	
<input type="checkbox"/> OATH	_____	
<input type="checkbox"/> 312	_____	
<input checked="" type="checkbox"/> SPEC	<u>12/29/00</u>	

[RUSH] MESSAGE:

Please provide missing Serial numbers on page 1, lines 6 and 11.

Thank you

[XRUSH] RESPONSE:

DONE

INITIALS: [Signature]

TECHNIQUE FOR OPTICALLY CONVERTING WAVELENGTHS
IN A MULTI-WAVELENGTH SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This patent application is related to U.S. Patent Application No. 09750316 (Attorney Docket No. 57983-000015, Client Reference No. 12922RO), filed concurrently with this patent application, and which is hereby incorporated by reference herein in its entirety.

10 This patent application is also related to U.S. Patent Application No. 09749946 (Attorney Docket No. 57983-000018, Client Reference No. 12946RO), filed concurrently with this patent application, and which is hereby incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

15 The present invention relates generally to optical wavelength conversion and, more particularly, to a technique for optically converting wavelengths in a multi-wavelength system.

BACKGROUND OF THE INVENTION

20 All-optical wavelength conversion is an important feature of multi-wavelength optical systems such as wavelength-switching networks. Solutions to provide all-optical wavelength conversion have been studied to a great extent in the context of wavelength-switching, because they simplify network management, and provide superior blocking performance (see B. Ramamurthy and B. Mukherjee, "Wavelength-conversion in WDM networking", IEEE Journal on Selected Areas on Communications, vol. 16, pages 1061-1073, September 1998). These solutions